

**Mutual Aid Box Alarm System – Illinois
Communications – MEDICAL HELICOPTERS**

Index #B-04-02

Adopted – 10/16/2002

Revised:

Page 1 of 2

Subject: Medical Helicopters
Functional Area: Communications
Category: Policy

Approved By: MABAS Executive Board

Purpose:

To recommend the use of MERCI or IREACH radio frequencies for medical helicopter landing zones.

Responsibility:

This policy applies to all MABAS member agencies. It is encouraged that all fire departments and related emergency response organizations throughout Illinois adopt the procedures set forth herein.

Accountability:

Enforcement of this specific policy rests initially with the Co-Chairs of the MABAS Telecommunications, Communications, and Dispatch Centers committee, then the MABAS CEO, followed by the MABAS President, 1st Vice President and 2nd Vice President.

Reporting Requirement:

There is no routine reporting requirement for this policy.

1. Background

Fire Departments frequently request medical evacuation helicopters to the scenes of accidents and other emergencies. It has become the “norm” for these helicopters to use the IFERN (154.265 MHz) frequency for landing zone coordination with the requesting fire department.

Experience has shown that the use of IFERN by medical helicopters is less than desirable. Helicopters landing at scenes where MABAS Box Alarm incidents are in progress can disrupt necessary communications with the MABAS Division, other responding units, staging, etc. Likewise, other incident related radio traffic can interfere with safety related transmissions between the landing zone sector and the medical helicopter.

Radio communications from medical helicopters while in flight can cover great geographic areas due to their antenna height. Helicopters responding to an incident in one jurisdiction can cause, or receive, harmful interference to/from an in-progress MABAS box alarm in another jurisdiction.

2. Policy

The MABAS Telecommunications, Communications and Dispatch Committee hereby makes the following recommendations for communications between fire department units and medical helicopters:

- A. The use of IFERN (154.265 MHz) or RED, WHITE or BLUE fireground frequencies for medical evacuation helicopter landing zones is an inappropriate use of the frequency and is strongly discouraged.
- B. The use of existing VHF-MERCI or IREACH frequencies is more appropriate for landing zone or ambulance to helicopter communications.
- C. For areas that use MERCI 340 (155.340 MHz) as their primary ambulance to hospital frequency, MERCI 400 (155.400 MHz) for communications with medical helicopters should be considered. (Areas south of North Avenue in the Chicago metropolitan area.)

**Mutual Aid Box Alarm System – Illinois
Communications – MEDICAL HELICOPTERS**

Index #B-04-02

Adopted – 10/16/2002

Revised:

Page 2 of 2

- D. For areas that use MERCI 400 (155.400 MHz) as their primary ambulance to hospital frequency, MERCI 340 (155.340 MHz) for communications with medical helicopters should be the frequency of choice. (Areas north of North Avenue in the Chicago metropolitan area.)
- E. Departments should consult with their EMS System to determine if the use of Tone Coded Squelch (PL) is desired to allow monitoring of landing zone activities by Medical Control.
- F. Departments without EMS responsibilities, or departments where use of existing VHF-MERCI frequencies is undesirable for helicopter use, IREACH (155.055 MHz) should be the frequency of choice for landing zone communications.

3. Conclusion

Proper use of available radio frequencies can eliminate harmful interference between MABAS incidents and medical helicopters. Nothing in this statement is intended to discourage the use of other licensed frequencies not specified herein for use during helicopter landing zone situations.